

E22-258^{Q&As}

XtremIO 3.x Flash Storage Solutions

Pass EMC E22-258 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e22-258.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



QUESTION 1

In an XtremIO environment, what is the minimum number of data bits that can be different in an incoming 8 KB block before the data is given its own unique fingerprint value?

- B. 2
- C. 4
- D. 8

Correct Answer: A

QUESTION 2

Which parameter can be changed to improve performance on an XtremIO array?

- A. HBA execution throttle
- B. RAID level
- C. Cache size
- D. Target port affinity

Correct Answer: A

QUESTION 3

Which options are available to an XtremIO administrator when a snapshot is created?

- A. Name the snapshot and select the parent folder
- B. Create a new folder and allocate space to the new folder
- C. Verify the snapshot name and configure the maximum snapshot size
- D. Select a parent folder and choose full copy or pointer-based copy

Correct Answer: A

QUESTION 4

What is the purpose of the TECH port on an XtremIO system?

- A. Connect to a storage controller or physical XMS and launch the easy-install configuration procedure
- B. Connect to a storage controller or physical XMS and configure a virtual XMS management interface

- C. Connect to a storage controller or physical XMS and launch the customer GUI or CLI
- D. Connect to a storage controller or physical XMS to configure the InfiniBand management interfaces

Correct Answer: A

QUESTION 5

What is the size of the data blocks sent to the SSDs after processing by the XtremIO storage controller if the XtremIO array is configured with 3.0.x code?

- A. 1 KB
- B. 2 KB
- C. 4 KB
- D. 8 KB

Correct Answer: D

QUESTION 6

Which VAAI feature can prevent blue screens on Microsoft Windows VMs that use XtremIO storage?

- A. TPSTUN
- B. Space Reclamation
- C. Atomic Test and Set
- D. Extended Copy

Correct Answer: A

QUESTION 7

Which XtremIO configuration options provide both Connect-In and Connect-Home functionality?

- A. ESRS IP Client and ESRS Gateway
- B. Email and FTPS
- C. ESRS IP Client and FTPS
- D. Email and ESRS Gateway

Correct Answer: A

QUESTION 8

How is the VM-based XtremIO Management Server (XMS) distributed?

- A. Open Virtual Appliance image
- B. ISO images of the OS and the XMS application
- C. ZIP file of the OS and the XMS application
- D. GZIP bundle of the application, OS, and VMware Player

Correct Answer: A

QUESTION 9

How many SSDs are located in each XtremIO storage controller?

- A. 0
- B. 1
- C. 2
- D. 4

Correct Answer: C

QUESTION 10

What is the default disk configuration for an XtremIO DAE?

- A. A single disk group in a 23+2 configuration
- B. Five private RAID Groups of five disks each
- C. A group of 12 disks and another of 13 disks
- D. Three private RAID Groups of eight disks each with a spare

Correct Answer: A

QUESTION 11

Which operating system and server type are required for installing the XMCLI client?

- A. CentOS 6.x, 64-bit, and either a physical or virtual server
- B. CentOS 6.x, 64 or 32-bit, and either a physical or virtual server
- C. CentOS 6.x, 64-bit, and physical server only

D. CentOS 6.x, 64 or 32-bit, and virtual server only

Correct Answer: A

QUESTION 12

A host with two HBAs is zoned to an XtremIO two X-Brick cluster through two FC switches. Which zone set meets the requirements for high availability?

A. Switch 1: HBA0 to X1-SC1-FC1, X1-SC2-FC1, X2-SC1-FC1, X2-SC2-FC1 Switch 2: HBA1 to X1-SC1FC2, X1-SC2-FC2, X2-SC1-FC2, X2-SC2-FC2

B. Switch 1: HBA0 to X1-SC1-FC1, X1-SC1-FC2, X2-SC1-FC1, X2-SC1-FC2 Switch 2: HBA1 to X1-SC2FC1, X1-SC2-FC2, X2-SC2-FC1, X2-SC2-FC2

C. Switch 1: HBA0 to X1-SC1-FC1, X1-SC1-FC2, X2-SC2-FC1, X2-SC2-FC2 Switch 2: HBA1 to X1-SC2FC1, X1-SC2-FC2, X2-SC1-FC1, X2-SC1-FC2

D. Switch 1: HBA0 to X1-SC2-FC1, X1-SC2-FC2, X2-SC1-FC1, X2-SC1-FC2 Switch 2: HBA1 to X1-SC1FC1, X1-SC1-FC2, X2-SC2-FC1, X2-SC2-FC2

Correct Answer: A

QUESTION 13

On an XtremIO system with a dual X-Brick topology, which hardware device should be in the upper-most position?

A. InfiniBand switch

B. Storage Controller 4

C. Battery Backup Unit 2

D. DAE 2

Correct Answer: A

QUESTION 14

How many minutes of information can be displayed by the latency monitor with the XtremIO GUI?

A. 5

B. 10

C. 15

D. 30

Correct Answer: D

QUESTION 15

How does VMware HA protect the XtremIO Management Server (XMS)?

- A. Restarts XMS VM on another host if a host failure occurs
- B. Runs two XMS VMs in lock-step mode for redundancy
- C. Migrates XMS VM data to another datastore if a storage failure occurs
- D. Maintains copies of the XMS VM data on two datastores for redundancy

Correct Answer: A

[Latest E22-258 Dumps](#)

[E22-258 Practice Test](#)

[E22-258 Study Guide](#)