

H31-124_V2.0^{Q&As}

HCIP Carrier IP V2.0

Pass Huawei H31-124_V2.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/h31-124_v2-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which of the following statements are correct?

- A. Both TE FRR and VPN FRR are used to protect tunnels, and therefore they can replace each other.
- B. After VPN FRR is deployed, the end-to-end service convergence time is shorter than 1 second.
- C. TE FRR Implements quick traffic switchovers if a PE becomes faulty.
- D. VPN FRR implements quick traffic switchovers if a PE becomes faulty.

Correct Answer: B

QUESTION 2

Which of the following statements about layer 2 LAN switch are incorrect?

- A. LAN switch will modify the data link layer header of the packet and then forward it.
- B. LAN switch can learn Mac address automatically.
- C. LAN switch operates at data link layer.
- D. LAN switch will modify the network layer header of the packet and then forward it.

Correct Answer: B

QUESTION 3

In BGP4+, both the NUU field and next-hop attribute can be expressed with an IPv6 address and prefix.

- A. True
- B. False

Correct Answer: A

QUESTION 4

The VRRP advertfse-Interval is 2s, preempt mode is enabled, Delay Time is 3s, then which of the following is the Master_Down_Interval time?

- A. 2s
- B. 4s
- C. 9s

D. 6s

Correct Answer: A

QUESTION 5

PIM-SM relies on particular unicast routing protocol for RPF check.

A. True

B. False

Correct Answer: B

QUESTION 6

Which of the following operations need to be complete before IP FRR configuration?

A. Configure different costs to generate two routes with different costs.

B. Configure the same cost to generate two equal-cost routes.

C. Configure a dynamic routing protocol on the entire network to Implement IP connectivity between nodes.

D. Configure static routes or an IGP to implement IP connectivity between nodes.

Correct Answer: C

QUESTION 7

When router receives two instances of one LSA at the same time, it will first compare LS age, If same ,Uien compare LS Sequence number.

A. True

B. False

Correct Answer: B

QUESTION 8

The following commands ate configured on the router running BGP:

```
bgp 100 peer 12.12.12.2 as-number 200 ipv4familyunicast network 1,1.1.1 255.255.255.255 undo synchronization peer 12.12.12.2 enable peer 12.12.12.2 next-hop-local
```

The IP address of the router's interface connected with peer 12.12.12.2 is 12.12.12.1.

What's the function of the command "peer 12.12.12.2 next-hop-local"?

- A. Change the next hop of the routes generated locally as 12.12.12.1
- B. This command does not work at all
- C. Change the next hop of the routes advertised to peer 12.12.12.2 as 12.12.12.1
- D. Change the next hop of the routes received from peer 12.12.12.2 as 12.12.12.2

Correct Answer: D

QUESTION 9

Which of the following MPLS TE components is used to set up tunnel?

- A. Path calculation
- B. Information distribution
- C. Packet forwarding
- D. Signaling

Correct Answer: B

QUESTION 10

Which of the following multicast IP addresses is administratively scope address?

- A. 224.0.0.0-224.0.0.255
- B. 239.0.0.0-239.0.0.255
- C. 224.0.1.0-238.255.255.255
- D. 224.0.0.0-239.255.255.255

Correct Answer: D

[H31-124 V2.0 VCE Dumps](#) [H31-124 V2.0 Practice Test](#) [H31-124 V2.0 Study Guide](#)