

H31-341^{Q&As}

HCIP-Transmission V2.5

Pass Huawei H31-341 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/h31-341.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which of the following monitoring boards do not support 1588v2 signal processing and transparent transmission?

- A. AST2
- B. SC2
- C. ST2
- D. SCI

Correct Answer: C

QUESTION 2

Which of the following statements about avoiding the generation of discrete trails are correct?

- A. Use the trail function for configuration.
- B. For services configured on a per-NE basis, search for trails on the NMS to ensure that the service configurations are complete and standard.
- C. A fiber cut or switching test must be performed on the trail with protection routes to ensure that the configuration is complete and standard.
- D. Guide users to learn service configuration specifications.

Correct Answer: D

QUESTION 3

Which of the following standards must be met for the isolation test in the feature test of the multiplexer/ demultiplexer?

- A. 25dB
- C. >20dB
- D.