

NCIDQ^{Q&As}

National Council for Interior Design Qualification

Pass Test Prep NCIDQ Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leadspass.com/ncidq.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Test Prep
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

The final responsibility of awarding a contract rests with the _____.

- A. Interior designer
- B. Construction manager
- C. Owner
- D. Owner's legal counsel

Correct Answer: C

QUESTION 2

In which space is emergency lighting REQUIRED?

- A. Elevators
- B. Private offices
- C. Egress corridors
- D. Restrooms

Correct Answer: C

QUESTION 3

After construction on a project has begun, the client asks you to change the wallcovering originally specified to one that does not meet current code requirements.

Which of the following is your BEST course of action?

- A. Research available products that are similar to the requested product and meet the code requirements. Present the options to the client for approval.
- B. Write a letter to the client stating that the change is against your professional recommendation and that you will make the change but assume no liability.
- C. Write a letter to the client explaining that you will not make the requested change.
- D. Tell the client that you will remove the wallcovering from the project and that the client may select and install a different product after your work is completed.

Correct Answer: A

QUESTION 4

The two most important factors in determining the number of exits required for a particular room or space are _____.

- A. Occupancy and the distance from the room exit to the building exit
- B. The exit widths and common path of egress travel
- C. The occupant load and building size
- D. The occupancy and the occupant load

Correct Answer: D

QUESTION 5

Certified contractors are required to abate all of the following hazardous materials EXCEPT _____.

- A. Asbestos
- B. Lead
- C. PCBs
- D. Radon

Correct Answer: D

QUESTION 6

When the owner wants to make sure some amount of money is included in the bid for as-yet known materials, the interior designer should use _____.

- A. An allowance
- B. An add-alternative
- C. A material bond
- D. A unit price

Correct Answer: A

QUESTION 7

The absolute minimum fresh air ventilation rate recommended by ASHRAE Standard 62 is _____.

- A. 5 cfm/person (3 L/s/person)
- B. 10 cfm/person (5 L/s/person)
- C. 15 cfm/person (8 L/s/person)

D. 20 cfm/person (10 L/s/person)

Correct Answer: C

QUESTION 8

How do you ensure that all signage on a construction project will be installed in the correct locations?

- A. Plan to be on site during installation of the signage, and specify where each sign will be placed.
- B. Require the signage vendor to provide detailed specifications.
- C. Provide a detailed takeoff along with a floor plan for installation.
- D. Schedule a meeting for the client or building owner to specify where signage will be placed.

Correct Answer: C

QUESTION 9

When creating a drawings that will be used for reproduction in a magazine, it is best to use _____.

- A. An architect's scale
- B. An engineer's scale
- C. A graphic scale
- D. A metric scale

Correct Answer: C

QUESTION 10

At the end of a commercial project, why should you require the HVAC system to be balanced?

- A. To verify that air quality levels are within the design specifications
- B. To detect significant air leaks in ductwork
- C. To adjust air flow at each device location to meet the criteria in the engineer's design
- D. To determine that each office is receiving the amount of outside air required by the design

Correct Answer: C

[Latest NCIDQ Dumps](#)

[NCIDQ VCE Dumps](#)

[NCIDQ Braindumps](#)