

VCS-273^{Q&As}

Administration of Veritas NetBackup 7.6.1 and NetBackup Appliances
2.6.1

Pass Veritas VCS-273 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/vcs-273.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Veritas
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A NetBackup appliance administrator observes poor performance on backups to an MSDP pool. The job details indicate bpbkar is waiting for empty buffers. Where should the administrator tune the appliance?

- A. NetBackup DataBuffers Size Defaults
- B. Deduplication Maximum Bandwidth
- C. Limit I/O streams for the disk pool
- D. NetBackup DataBuffers Size Disk

Correct Answer: D

QUESTION 2

Which command should an administrator use to determine which storage lifecycle policy's image copies are incomplete?

- A. nbstl
- B. nbreplicate
- C. bpimage
- D. nbstlutil

Correct Answer: C

QUESTION 3

Which utility should an administrator use to verify library device functionality?

- A. nbdevconfig
- B. robtest
- C. bpmedia
- D. tpconfig

Correct Answer: C

QUESTION 4

Where should an administrator look in the NetBackup Administration Console to determine whether an AdvancedDisk storage server is configured?

- A. Media and Device Management > Credentials > Disk Array Hosts
- B. Media and Device Management > Device Monitor > Storage Servers
- C. Media and Device Management > Devices > Storage Servers
- D. Media and Device Management > Credentials > Storage Servers

Correct Answer: D

QUESTION 5

An administrator working offsite is required to carry out a major upgrade to a NetBackup appliance. The appliance will need to be rebooted multiple times during the upgrade process. How should the administrator connect to the appliance?

- A. connect to the IPMI interface using a web browser
- B. connect to the serial interface remotely using CLISH
- C. connect to the IPMI interface using the appliance web UI
- D. connect to the serial interface remotely using SSH

Correct Answer: A

QUESTION 6

An administrator needs to duplicate a backup that completed successfully earlier that same day. How can this be accomplished?

- A. locate the original backup from NetBackup Management > Reports > Images on Media, right click and select duplicate
- B. locate the policy for the original backup and initiate a manual backup
- C. locate the original backup in the activity monitor, right click and select restart
- D. locate the original backup from NetBackup Management > Catalog, right click and select duplicate

Correct Answer: D

QUESTION 7

What is the default length of time that true image restore (TIR) information is retained in the NetBackup catalog?

- A. 1 day
- B. 3 days
- C. 28 days
- D. 30 days

Correct Answer: A

QUESTION 8

What is the image removal behavior for relocated images from a disk staging storage unit when the high water mark is reached during a backup?

- A. NetBackup removes the oldest images until the low water mark is reached.
- B. NetBackup removes images alphabetically until the low water mark is reached.
- C. NetBackup removes the largest images until the low water mark is reached.
- D. NetBackup removes images with the lowest rank data classification until the low water mark is reached.

Correct Answer: A

QUESTION 9

Which command should an administrator run to display all images written to both disk and tape for a particular client?

- A. bplist
- B. bpimmedia
- C. bpimage
- D. bpstulist

Correct Answer: B

QUESTION 10

Which NetBackup utility should an administrator use to determine I/O performance of the appliance storage and network?

- A. nbperfchk
- B. nbdna
- C. datacollect
- D. nbsu

Correct Answer: A

QUESTION 11

Which volume pool must be manually created in NetBackup?

- A. NetBackup
- B. DataStore
- C. Scratch
- D. CatalogBackup

Correct Answer: C

QUESTION 12

A VMware policy has been configured to back up a Linux virtual machine. Which condition must be met to ensure all data is flushed from memory to disk?

- A. SYMCquiesce utility must be installed
- B. exclude swap and paging files must be unchecked
- C. the virtual machine must be running RedHat Enterprise Linux
- D. VMware Tools services must be stopped

Correct Answer: A

QUESTION 13

Which parameter in NetBackup Management > Host Properties must be modified to change the logging level to 5 for client1.domain?

- A. Master Servers > [master_server_name] > Logging > Global logging level
- B. Clients > [client_name] > Logging > Global logging level
- C. Master Servers > [master_server_name] > Logging > Enable robust logging
- D. Clients > [client_name] > Logging > Enable robust logging

Correct Answer: B

QUESTION 14

A tape library had the robot firmware upgraded and now the robot is reading the barcodes with additional characters.

How should an administrator enable NetBackup 7.6.1 to use the same characters as before the firmware upgrade occurred?

- A. update the Media ID Generation setting
- B. update Media settings
- C. update Device mappings
- D. update the Barcode Rules setting

Correct Answer: A

QUESTION 15

An administrator needs to back up 100 clients using 10 LTO5 tape drives. Which policy setting will perform the backup fastest?

- A. Allow multiple data streams
- B. Limit jobs per policy
- C. Media multiplexing
- D. Use Accelerator

Correct Answer: C

[Latest VCS-273 Dumps](#)

[VCS-273 VCE Dumps](#)

[VCS-273 Practice Test](#)